



US006251478B1

(12) **United States Patent**  
**Pacifico et al.**

(10) **Patent No.:** **US 6,251,478 B1**  
(45) **Date of Patent:** **Jun. 26, 2001**

(54) **SENSITIVE SUBSTANCE ENCAPSULATION**

(75) **Inventors:** Carl J. Pacifico, West Milford, NJ  
(US); Wen-Hsin Wu, Middletown;  
Marta Fraley, Parksville, both of NY  
(US)

(73) **Assignee:** Balchem Corporation, Slate Hill, NY  
(US)

(\*) **Notice:** Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 09/469,368

(22) **Filed:** Dec. 22, 1999

(51) **Int. Cl.<sup>7</sup>** ..... B01J 13/02; A61K 9/16;  
B65B 1/04

(52) **U.S. Cl.** ..... 427/213.3; 424/1.29; 424/1.69;  
424/1.73; 424/451; 424/463; 424/490; 424/491;  
424/493; 424/496; 426/89; 426/96; 426/98;  
426/100; 426/235

(58) **Field of Search** ..... 424/1.29, 1.69,  
424/1.73, 451, 463, 490, 491, 493, 496;  
427/213.3; 426/89, 96, 98, 100, 235

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,857,964 12/1974 Yolles .  
4,232,047 \* 11/1980 Sair et al. .... 426/96

4,532,145	7/1985	Saleeb et al. .	
4,576,737	3/1986	Johnson .	
4,576,826	3/1986	Liu et al. .	
4,689,235 *	8/1987	Barnes et al. ....	426/89
4,828,857	5/1989	Sharma et al. .	
5,004,595	4/1991	Cherukuri et al. .	
5,009,900 *	4/1991	Levine et al. ....	426/96
5,399,368	3/1995	Garwood et al. .	
5,460,756	10/1995	Redding, Jr. .	
5,496,574	3/1996	Rushmore et al. .	
5,506,353	4/1996	Subramaniam .	
5,558,889	9/1996	Rossi .	
5,580,593	12/1996	Liu et al. .	
5,601,865	2/1997	Fulger et al. .	
5,603,971	2/1997	Porzio et al. .	
5,607,708	3/1997	Fraser et al. .	
5,705,207	1/1998	Cook et al. .	
5,756,136	5/1998	Black et al. .	
5,792,505	8/1998	Fulger et al. .	
5,874,102	2/1999	LaJoie et al. .	

\* cited by examiner

*Primary Examiner*—Samuel A. Acquah

(74) *Attorney, Agent, or Firm*—Banner & Witcoff, Ltd.

(57) **ABSTRACT**

A process for stabilizing a sensitive substance; (a) plating a sensitive substance onto a solid carrier under a controlled atmosphere to reduce loss of the sensitive substance; (b) encapsulating the plated material under controlled atmosphere and airflow to reduce volatilization during the process and stabilize the sensitive substance.

**20 Claims, No Drawings**